

JIS B 1111

H形十字穴付き 皿頭小ねじ

TYPE H FLAT HEAD MACHINE SCREW

unit : mm

Screw Size	Cross Recess No.	dk		k		c	m	q		Punch No.	Punch Diameter (D)
		Basic Size	Tolerance	Basic Size	Tolerance	Approx.	Ref.	Max.	Min.		
M2	1	4	0 -0.4	1.2	0 -0.2	0.2	2.2	1.01	0.65	JPHM20F	12
(M2.2)		4.4		1.3		0.2	2.4	1.21	0.85	JPHM23F	12
(M2.3)		4.6		1.35		0.2	2.4	1.21	0.85	JPHM26F	12
M2.5		5		1.45		0.2	2.6	1.42	1.05		12
(M2.6)		5.2		1.5		0.2	2.6	1.42	1.05		12
M3	2	6	0 -0.5	1.75	0 -0.3	0.25	3.6	1.43	0.91	JPHM30F	12
(M3.5)		7		2		0.25	4.1	1.93	1.40	JPHM35F	14
M4		8		2.3		0.3	4.5	2.33	1.79	JPHM40F	14
(M4.5)		9		2.55		0.3	4.9	2.73	2.19	JPHM45F	14
M5		10		2.8		0.3	5.1	2.93	2.38	JPHM50F	14
M6	3	12	0 -0.7	3.4	0 -0.4	0.4	6.7	3.26	2.70	JPHM60F	18
M8		16	0 -0.8	4.4		0.4	8.4	4.96	4.36	JPHM80F	23

